

Product profile

PM4i

EasyCoder® Printer



- Superior throughput eliminates wait time at the printer
- Heavy-duty metal construction withstands harsh/rugged environments
- Integrated EasyLAN™ Ethernet, USB and serial interface standard
- Compact Flash memory for quick and easy firmware, font and memory upgrades
- Supports stand-alone printer applications
- Easily adapts to changing host environments and applications
- Utilize up to six interface ports simultaneously, including internal EasyLAN Wireless
- Magnetic QuickMount™ printhead for easy printhead installation
- User selectable printer language
- Double-clutching ribbon mechanism supports ribbons wound in either direction

Are you looking for more efficient processes, reduced costs, and increased production?

The EasyCoder PM4i is an industrial printer designed to excel in demanding applications and environments. Utilizing the latest technology, the PM4i features a strong and proven mechanical platform, and powerful newly developed electronics.

The EasyCoder PM4i printer acts as a “smart client” executing user-defined programs. This means your PM4i printer eliminates the personal computer, operates additional hardware (e.g. scanners, other printers, conveyors), accesses information from network host, and retains the ability to change as needed with the application for additional functionality. When using the EasyLAN™ Wireless option for the PM4i, any attached peripheral devices also become part of the wireless infrastructure.

Printer command languages do not restrict the EasyCoder PM4i bar code label printer. The printer can be changed to understand and replace competitive and older Intermec printers without requiring any changes to the host programming or label formats that are currently being used.

The EasyCoder PM4i includes integrated wired or wireless EasyLAN networking. The EasyLAN Wireless interface uses an integrated standard 802.11b radio. This radio provides 128-bit WEP encryption of the information relayed through the network. Intermec’s wired and wireless technology ensures secure printing and network infrastructure for all environments.

This is an extremely versatile bar code label printer. There are up to six interface ports that can be used simultaneously. The EasyCoder PM4i includes serial, parallel, USB, internal EasyLAN Ethernet, and EasyLAN Wireless. The magnetic QuickMount printhead eliminates hassles and the need to call a service technician. The printhead is replaced quickly and easily with the magnet and u-brackets ensuring proper alignment. The double-clutching ribbon mechanism means that you are no longer restricted to ribbon types based on how they are wound. The handy, inexpensive and PC-compatible Compact Flash memory technology provides quick and easy upgrades of firmware, fonts and memory.

The EasyCoder PM4i printer is exceptionally fast in throughput and printing, reliable, and delivers very high print quality.

Application

Direct Thermal and Thermal Transfer label, ticket and tag printer.

Physical Characteristics

LxHxW: 54.3 x 26.1 x 29.8 cm (21.38 x 10.28 x 11.73 in)
Weight: 13.5 kg (29.76 lbs.)

Print Specifications

Max. Width: 104 mm (4.09 in) at 203 dpi; 105.7 mm (4.16 in) at 300 dpi.

Max. Length w/ std memory: 2520 mm (99.2 in) at 203 dpi; 1092 mm (43.0 in) at 300 dpi.

Max length w/ 16MB SDRAM: 4095 mm (161.2 in) at 203 dpi; 2730 mm (107.5 in) at 300 dpi.

Print Speed

Up to 76 labels per minute. 101x152mm (4x6 in) GM1724 label. To learn more about print speed, please visit www.intermec.com/printspeed.
Vitesse d'impression.

Print Direction

Prints smooth text, any size bar codes and graphics in all four orthogonal directions.

Print Resolution

8 dots/mm (203 dpi); 11.8 dots/mm (300 dpi)

Label/Ticket/Tag

Max. Width: 114.3 mm (4.5 in)

Min. Width: 25.4 mm (1 in)

Thickness: 2.5 to 7 mil

Style: Roll-fed, die-cut, continuous or fanfold labels, tags or tickets

Label Roll max diameter: 213 mm (8.38 in)

Label Roll Core: 38-76 mm (1.5-3 in)

Media Type: Thermally sensitive media

Ribbon Roll

Ribbon roll max diameter: 83 mm (3.27 in) or approx.

450 m (1475 ft) of ribbon

Ribbon Roll Core: 25 mm (1 in)

Ribbon Type: Wax, wax/resin, resin

Interface

Standard:

RS-232, up to 115.2 kB/s

USB 1.1

EasyLAN Internal Ethernet 100/10BaseT

I2C-bus for cutter

Wand interface for EasySet™ System

Optional:

• EasyLAN Wireless, internal 802.11b Wireless Ethernet

Optional interface card adapters (any 2 can be fitted simultaneously):

• Parallel IEEE 1284

- Industrial Interface (8 digital in/out, 4 analog relays, 1 RS232/422/485 port)
- Dual Serial ports RS-232, RS-422, RS-485 and 20mA Current Loop

EasyLAN Ethernet Network Interface:

Internal High Speed Ethernet

Ethernet: RJ-45 connector for 10baseT

Ethernet or 100baseTX Fast Ethernet

Supported protocols: TCP/IP-suite (TCP, UDP, ICMP, IGMP, etc.), LPR/LPD, FTP, BOOTP, DHCP, HTTP, SNMP, SMTP.

SNMP-MIB II supported (over UDP/IP), private enterprise MIB included

EasyLAN Wireless

- Fully integrated IEEE 802.11b
- WEP 128 bit
- Supports IEEE 802.1x security
- Multiple industrial antenna options for maximized coverage

Software

Available printer command languages:

- IPL
- Fingerprint/Direct Protocol

Applications/Drivers (comes on Printer Companion CD) including:

- InterDriver™ Windows printer driver
 - Intermec LabelShop® START label design and print package
 - Intermec Printer Network Manager for administration of network connected printers
 - PrintSet for printer configuration
- Optional software for application development:
- Fingerprint ApplicationBuilder
 - Intermec Printer Application Server • ERPLabel for SAP R/3.

Bar Code Symbolologies

1-dimensional: Code 2 of 5, Codabar, Code 11, Code 39, Code 93, Code 128, Interleaved 2 of 5, Straight 2 of 5, Matrix 2 of 5, Postnet, Code One, UPC/EAN, JIS-ITF
2-dimensional: Code 16K, Code 49, DataMatrix, PDF417, QR Code, MicroPDF417, MaxiCode, Plessey, MSI

Standards Supported

UPC/EAN Shipping Container; UCC/EAN 128 Serial Shipping Container; MH10.8 Shipping Label; AIAG (shipping parts label); LOGMARS; POSTNET; HIBCC; ISBT 128; GM1724; UPS shipping label; Global Transport label

Characters Sets

Fingerprint/DP: 15 TrueType™ fonts including 12 UNICODE (1 WGL4), 1 symbol, 1 OCR-A, 1 OCR-B. All fonts are scalable. Font cache for maximum performance. ATF font support. IPL firmware: 3 TrueType fonts and 20 bitmap fonts. Non-Latin fonts are available as options.

Graphics

Supports PCX file format.

Memory

Standard: 4MB Flash

8 MB SDRAM

1 Compact Flash slot

Optional: Additional FLASH memory up to 16MB (8+8)

1 GB Compact Flash memory

Protocol

Fingerprint/Direct Protocol:

XON/XOFF, ENQ/ACK, DTR, RTS/CTS

IPL: XON/XOFF, Intermec Std. Protocol

Display

Back-lit LCD for 2x16 characters and 3 LED indicator lamps
Keypad Control Panel

- Full keypad control panel (Fingerprint/DP)
- Reduced keypad control panel (IPL)

Power Supply

115/230VAC auto-switch w/PFC

Voltage range: 90-264VAC.

Frequency Range: 45-65 MHz

Operating Environment

Temperature: +5°- 40°C (+40°- 104°F)

Humidity: 20-80% RH non-condensing

Noise: 50 dB (printing), no noise standby

Regulatory Approvals

CE (EN55022 Class A), FCC Class A, UL, CSA, C-Tick

Options

Integral Self-Strip unit with Liner Takeup, Label Taken Sensor (LTS), Compact Flash (CF) memory, Flash and SDRAM SIMM memory, Various International Double Byte Fonts, EasySet bar code Wand*, External RS-232C alphanumeric keyboard*, Parallel Interface board, Additional Serial Interface board, Industrial Interface board*, Real Time Clock, Media supply hub, Cutter, Label low sensor

*Not applicable when using IPL firmware



LOGICODE SA

Str. Mihai Romănu nr. 5B,
400495 Cluj-Napoca
Tel: 0364 409108,
0731 307621
informatii@logiccode.ro
www.logiccode.ro



Copyright © 2007 Intermec Technologies Corporation.
Tous droits réservés. Intermec est une marque déposée d'Intermec Technologies Corporation. Toutes les autres marques déposées citées sont les propriétés de leur société propriétaire. imprimé en France.
611518-D 12/07

Dans un souci d'une amélioration constante de ses produits, Intermec Technologies Corporation se réserve le droit de modifier les spécifications de ceux-ci sans préavis.